PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:		(1	1) International Publication Number:	WO 00/58975
H01B 3/44	A1	(4	3) International Publication Date:	5 October 2000 (05.10.00)
 (21) International Application Number: PCT/EP (22) International Filing Date: 21 February 2000 ((30) Priority Data: 60/126,100 25 March 1999 (25.03.99) 09/370,293 9 August 1999 (09.08.99) (71) Applicant: CIBA SPECIALTY CHEMICALS H INC. [CH/CH]; Klybeckstrasse 141, CH-4057 Bas (72) Inventors: LUPIA, Joseph, Anthony; 8511 Quail Cre Colfax, NC 27235 (US). FAY, Joseph, James; 25 Lane, Hopewell junction, NY 12533 (US). 	21.02.0 U OLDIN sel (CH	US US VG H).	(81) Designated States: AE, AL, AM, BR, BY, CA, CH, CN, CR, CES, FI, GB, GD, GE, GH, GM, KE, KG, KP, KR, KZ, LC, LK MD, MG, MK, MN, MW, MX SD, SE, SG, SI, SK, SL, TJ, UZ, VN, YU, ZA, ZW, ARIPO MW, SD, SL, SZ, TZ, UG, ZW BY, KG, KZ, MD, RU, TJ, TM CH, CY, DE, DK, ES, FI, FR, NL, PT, SE), OAPI patent (BF GN, GW, ML, MR, NE, SN, T Published With international search report	CU, CZ, DE, DK, DM, EE, HR, HU, ID, IL, IN, IS, JP, LR, LS, LT, LU, LV, MA, NO, NZ, PL, PT, RO, RU, TM, TR, TT, TZ, UA, UG, D patent (GH, GM, KE, LS, L), European patent (AM, AZ, GB, GR, IE, IT, LU, MC, GB, GF, CG, CI, CM, GA, TD, TG).
(54) Title: STABILIZED TELECOMMUNICATION CA	BLE IN	NSU	ILATION COMPOSITION	

(57) Abstract

Polyolefin wire insulation in hydrocarbon grease filled telecommunications cable which is subsequently exposed in an outdoor interconnection box is especially vulnerable to the adverse conditions of heat, oxygen and moisture. The combination of one or more primary phenolic antioxidants selected from N,N'-hexane-1,6-diylbis-(3-(3,5-di-tert-butyl-4-hydroxyphenylpropionamide), tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate and tris(2-(3,5-di-tert-butyl-4-hydroxydrocinnamoyloxy)ethyl)isocyanurate together with one or more alkyhydroxyphenylalkanoil hydrazine metal deactivators is very effective towards providing oxidative stability for polyolefin wire insulation under these conditions.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
	AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
	AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
	ΑU	Australia	GA.	Gabon	LV	Latvia	SZ	Swaziland
	AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
	BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
	BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
	BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
	\mathbf{BF}	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
	BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
	BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
	BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
	BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
	CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
	CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
	CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
	CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
	CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
	CM	Cameroon		Republic of Korea	PL	Poland		
	CN	China	KR	Republic of Korea	PT	Portugal		
	CU	Cuba	KZ	Kazakstan	RO	Romania		
	CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
	DE	Germany	LI	Liechtenstein	SD	Sudan		
	DK	Denmark	LK	Sri Lanka	SE	Sweden		
	EE	Estonia	LR	Liberia	SG	Singapore		
-								

-1-

Stabilized Telecommunication Cable Insulation Composition

The present invention pertains to a polyolefin composition for use as insulation for wire and cable that has improved resistance to the deleterious effects of heat, oxygen and moisture. The stabilized compositions are suitable for use as telecommunications (telecom) cable.

A typical telecom cable is constructed of twisted pairs of polyolefin-insulated copper wire which are bundled together and protected by a cable sheath. The cable sheath is composed of a metal foil and/or armor in combination with a polymeric jacketing material. The entire system is referred to as "telecom cable".

To reduce the risk of water penetration into the cable system and to minimize the deleterious effects of moisture on the polyolefin insulation, the system is made water-tight by filling the voids in the cable with a hydrophobic grease. Cable systems of this type are described for example in U.S. Patent Nos. 3,888,709, 4,044,200, 4,218,577, 5,502,288 and European patent application 565,868 A2, and the references therein. The cable filler grease is known to extract stabilizers incorporated into the wire insulation. This is discussed for example in "Plastics Additives Handbook", 3rd Edition, R. Gächter, H. Müller, Eds., Hanser Publishers, pages 116-119 (1990)].

Junctions of two or more telecom cables are often required and this is accomplished in an outdoor enclosure known as a pedestal or an interconnection box. Inside the pedestal, the cable sheathing is removed, the cable filler grease is wiped off, and the transmission wires are joined as necessary. The exposed insulated wires are now subject to the adverse conditions of heat, oxygen and moisture. The polyolefin insulation, having lost a portion of its stabilizer additives to extraction by the filler grease, is especially vulnerable to these environmental conditions and may exhibit premature oxidative failure. This failure exhibits itself in the loss of physical properties of the insulation which ultimately results in a loss of electrical transmission performance.

The stabilization of polyolefin wire insulation in telecom applications with hindered phenolic antioxidants is known. A state of the art stabilizer system includes the use of a hindered phenol together with a metal deactivator such as Irganox® MD 1024, 1,2 -bis(3,5-di-

tert-butyl-4-hydroxyhydrocinnamoyl)hydrazine or Naugard® XL-1, 2,2'-oxalyldiamido-bis-[ethyl 3-(3,5-di-tert-butyl-4-hydroxylphenyl)propionate]. A typical stabilizer package includes, as the primary antioxidant, Irganox® 1010, pentaerythritol tetrakis [3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate], and as the metal deactivator, Irganox® MD 1024. This system is disclosed in European patent application 565,868 A2 and U.S. Patent Nos. 4,044,200, 5,380,591 and 5,575,952. Irganox® is a protected trade name of Ciba Specialty Chemicals Corp., Naugard® is a protected trade name of Uniroyal.

- U.S. Patent No. 4,044,200 discloses the stabilization of polyethylene wire insulation in the presence of a moisture barrier filler with a combination of an alkylhydroxyphenylalkanoyl hydrazide and/or a substituted amido triazole together with a high molecular weight hindered phenolic antioxidant. Specifically disclosed is the combination of Irganox® MD 1024 and Irganox® 1010.
- U.S. Patent No. 4,812,500 discloses a polyolefin composition having improved resistance to deterioration when exposed to hot oxygenated water, chlorinated water, and UV radiation. The composition comprises a hindered amine UV stabilizer, a hindered phenolic thermal stabilizer and a chelating (metal deactivating) agent. The hindered phenolic is selected from a specific group including Irganox® 1010, pentaerythritol tetrakis [3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate], and Irganox® 3114, tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate. The chelating agent is selected from a group including Irganox® MD 1024, 1,2 -bis(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyl)hydrazine. Irganox® is a trademark of Ciba Specialty Chemicals Corp. It is contemplated that the invention may be used for various systems where water or moisture are present, including wire and cable coatings. There is no mention of grease filled cable systems where the potential for extraction of the additives exists.
- U.S. Patent Nos. 5,380,591, 5,453,322, 5,575,952, 5,766,761 and 5,807,635 disclose the stabilization of hydrocarbon grease filled telephone cables with the combination of a mixture of an alkylhydroxyphenylalkanoyl hydrazine with a functionalized hindered amine. Irganox® MD 1024 is specifically disclosed as the hydrazine in each case.

- U.S. Patent No. 5,474,847 teaches the stabilization of polyolefin wire insulation in grease filled telephone cables with the reaction products of hydrazide derivatives of hindered phenols or hindered amines or amino derivatives of hindered amines with a quinone.
- U.S. Patent No. 5,502,288 discloses the stabilization of polyolefin wire insulation in telephone cables with the use of Irganox[®] MD 1024 or Naugard[®] XL-1 or mixtures thereof with selected antioxidants.

European patent application 565,868 A2 teaches the stabilization of polyolefin wire insulation compositions exposed to water-blocking cable fillers with a combination of divalent metal salts of phenolic carboxylic or phosphonic acids together with a metal deactivator. Specifically named metal deactivators are Irganox® MD 1024 and Naugard® XL-1. A preferred composition also includes the use of Irganox® 1010.

WO 93/24935 teaches the use of the reaction products of an anhydride of an unsaturated aliphatic diacid with one or more functionalized hindered amines and/or functionalized hindered phenols for the stabilization of polyolefin wire insulation in grease filled telephone cables.

WO 93/24938 discloses a grease filled cable construction in which the polyolefin wire insulation which has bonded to it, through an anhydride of an aliphatic diacid, one or more functionalized hindered amines and/or functionalized hindered phenols.

In order to protect the polyolefin wire insulation that is exposed to environmental conditions in the interconnection box, and to counteract the extraction of stabilizers by the cable filler grease, it has been suggested that high loadings of the stabilizer system be employed. There is a need to find more efficient primary antioxidant/metal deactivator combinations than those that are the state of the art in order to reduce the high cost associated with the use of these levels of stabilizers. Stabilizer efficiency in this context is the combined ability of the stabilizer system to resist extraction from the polyolefin wire insulation into the cable filler grease and to provide the polyolefin with resistance to the deleterious effects of heat, oxygen and moisture.

Surprisingly, it has been found that the combination of one or more primary phenolic antioxidants selected from Irganox® 1098, N,N'-hexane-1,6-diylbis-(3-(3,5-di-tert-butyl-4-hydroxyphenylpropionamide)), Irganox® 3114, tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate, and Irganox® 3125, tris(2-(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyloxy)ethyl) isocyanurate, together with one or more alkylhydroxyphenylalkanoyl hydrazine metal deactivators is especially effective towards providing oxidative stability for polyolefin wire insulation in grease filled telecom cables. Irganox® is a trademark of Ciba Specialty Chemicals Corp.

The present invention pertains to a novel hydrocarbon grease filled cable construction wherein the polyolefin wire insulation has improved oxidative stability.

More particularly, the novel cable construction of this invention comprises

- (i) a plurality of insulated electrical conductors having interstices therebetween, said insulation comprising
 - (a) one or more polyolefins, and
- (b) one or more primary antioxidants selected from the group of N,N'-hexane-1,6-diylbis-(3-(3,5-di-tert-butyl-4-hydroxyphenylpropionamide)), tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate and tris(2-(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyloxy)ethyl) isocyanurate, and
- (c) one or more metal deactivators selected from the alkylhydroxyphenylalkanoyl hydrazines, and
 - (ii) hydrocarbon cable filler grease within the interstices, and
 - (iii) a sheath surrounding components (i) and (ii).

WO 00/58975 PCT/EP00/01403

- 5 -

The polyolefins of component (a) are generally thermoplastic resins, which are crosslinkable. They can be homopolymers or copolymers produced from two or more comonomers, or a blend of two or more of these polymers, conventionally used in film, sheet, and tubing, and as jacketing and/or insulating materials in wire and cable applications. The monomers useful in the production of these homopolymers and copolymers can have 2 to 20 carbon atoms, and preferably have 2 to 12 carbon atoms. Examples of these monomers are alpha-olefins such as ethylene, propylene, 1-butene, 1-hexene, 4-methyl-1pentene, and 1-octene; unsaturated esters such as vinyl acetate, ethyl acrylate, methyl acrylate, methyl methacrylate, t-butyl acrylate, n-butyl acrylate, n-butyl methacrylate, 2ethylhexyl acrylate, and other alkyl acrylates; diolefins such as 1,4-pentadiene, 1,3hexadiene, 1,5-hexadiene, 1,4-octadiene, and ethylidene norbornene, commonly the third monomer in a terpolymer; other monomers such as styrene, p-methyl styrene, alpha-methyl styrene, p-chlorostyrene, vinyl naphthalene, and similar aryl olefins; nitriles such as acrylonitrile, methacrylonitrile, and alpha-chloroacrylonitrile; vinyl methyl ketone, vinyl methyl ether, vinylidene chloride, maleic anhydride, vinyl chloride, vinylidene chloride, vinyl alcohol, tetrafluoroethylene, and chorotrifluoroethylene; and acrylic acid, methacrylic acid, and other similar unsaturated acids.

The homopolymers and copolymers referred to can be non-halogenated, or halogenated in a conventional manner, generally with chorine or bromine. Examples of halogenated polymers are polyvinyl chloride, polyvinylidene chloride, and polytetrafluoroethylene. The homopolymers and copolymers of ethylene and propylene are preferred, both in the non-halogenated and halogenated form. Included in this preferred group are terpolymers such as ethylene/propylene/diene monomer rubbers.

Other examples of ethylene polymers are as follows: a high pressure homopolymer of ethylene; a copolymer of ethylene and one or more alpha-olefins having 3 to 12 carbon atoms; a homopolymer or copolymer of ethylene having a hydrolyzable silane grafted to their backbones; a copolymer of ethylene and alkenyl trialkyloxy silane such as trimethoxy vinyl silane; or a copolymer of an alpha-olefin having 2 to 12 carbon atoms and an unsaturated ester having 4 to 20 carbon atoms, e.g., an ethylene/ethyl acrylate or vinyl acetate copolymer; an ethylene/ethyl acrylate or vinyl acetate/hydrolyzable silane terpolymer; and ethylene/ethyl acrylate or vinyl acetate copolymers having a hydrolyzable silane grafted to their backbones.

With respect to polypropylene: Homopolymers and copolymers of propylene and one or more other alpha-olefins wherein the portion of the copolymer based on propylene is at least about 60 percent by weight based on the weight of the copolymer can be used to provide the polyolefin of the invention. Preferred polypropylene alpha-olefin comonomers are those having 2 or 4 to 12 carbon atoms.

Polyolefins, i.e. the polymers of monoolefins exemplified above, for example polyethylene and polypropylene, can be prepared by different, and especially by the following, methods:

- 1) radical polymerization (normally under high pressure and at elevated temperature).
- 2) catalytic polymerization using a catalyst that normally contains one or more than one metal of groups IVb, Vb, Vlb or VIII of the Periodic Table. These metals usually have one or more than one ligand, typically oxides, halides, alcoholates, esters, ethers, amines, alkyls, alkenyls and/or aryls that may be either p- or s-coordinated. These metal complexes may be in the free form or fixed on substrates, typically on activated magnesium chloride, titanium(III) chloride, alumina or silicon oxide. These catalysts may be soluble or insoluble in the polymerization medium. The catalysts can be used by themselves in the polymerization or further activators may be used, typically metal alkyls, metal hydrides, metal alkyl halides, metal alkyl oxides or metal alkyloxanes, said metals being elements of groups Ia, Ila and/or Illa of the Periodic Table. The activators may be modified conveniently with further ester, ether, amine or silyl ether groups. These catalyst systems are usually termed Phillips, Standard Oil Indiana, Ziegler (-Natta), TNZ (DuPont), metallocene or single site catalysts (SSC).

The homopolymer or copolymers can be crosslinked or cured with an organic peroxide, or to make them hydrolyzable, they can be grafted with alkenyl trialkoxy silane in the presence of an organic peroxide which acts as a free radical generator or catalyst. Useful alkenyl trialkoxy silanes include the vinyl trialkoxy silanes such as vinyl trimethoxy silane, vinyl triethoxy silane, and vinyl triisopropoxy silane. The alkenyl and alkoxy radicals can have 1 to 30 carbon atoms and preferably have 1 to 12 carbon atoms. The hydrolyzable polymers can be moisture cured in the presence of a silanol condensation catalyst such as

WO 00/58975

dibutyl tin dilaurate, dioctyl tin maleate, stannous acetate, stannous octoate, lead naphthenate, zinc octoate, iron 2-ethyl hexoate, and other metal carboxylates.

The homopolymers or copolymers of ethylene wherein ethylene is the primary comonomer and the homopolymers and copolymers of propylene wherein propylene is the primary comonomer may be referred to herein as polyethylene and polypropylene, respectively.

The polyolefins of component a) are preferably polyethylene or polypropylene or mixtures thereof.

The alkylhydroxyphenylalkanoyl hydrazines of component (c) are described in U.S. Patent Nos. 3,660,438 and 3,773,722. Preferably the compounds of component (c) are of the following structure:

$$R_1$$
 O N R_3 O N H R_3 R_2

wherein n is 0 or an integer from 1 to 5;

R₁ is a straight or branched chain alkyl having 1 to 6 carbon atoms;

R₂ is hydrogen or R₁; and

R₃ is hydrogen, an alkanoyl having 2 to 18 carbon atoms, or a group of the formula

$$R_1$$
 C
 $CH_2)_n$

wherein n, R₁ and R₂ independently have the same definitions as above.

The radical R₂ is preferably in the ortho-position to the OH group.

Preferably, the metal deactivator of component (c) is Irganox® MD 1024, 1,2 -bis(3,5-ditert-butyl-4-hydroxyhydrocinnamoyl)hydrazine, Ciba Specialty Chemicals Corp.

The hydrocarbon cable filler grease of component (ii) is a mixture of hydrocarbon compounds, which is semisolid at use temperatures. It is known industrially as "cable filling compound." A typical requirement of cable filling compounds is that the grease has minimal leakage from the cut end of a cable at a 60° C or higher temperature rating. Another typical requirement is that the grease resist water leakage through a short length of cut cable when water pressure is applied at one end. Among other typical requirements are cost competitiveness; minimal detrimental effect on signal transmission; minimal detrimental effect on the physical characteristics of the polymeric insulation and cable sheathing materials; thermal and oxidative stability; and cable fabrication processability.

Cable fabrication can be accomplished by heating the cable filling compound to a temperature of approximately 100° C. This liquefies the filling compound so that it can be pumped into the multiconductor cable core to fully impregnate the interstices and eliminate all air space. Alternatively, thixotropic cable filling compounds using shear induced flow can be processed at reduced temperatures in the same manner. A cross section of a typical finished grease filled cable transmission core is made up of about 52 percent insulated wire and about 48 percent interstices in terms of the areas of the total cross section. Since the interstices are completely filled with cable filling compound, a filled cable core typically contains about 48 percent by volume of cable filling compound.

The cable filling compound or one or more of its hydrocarbon constituents enter the insulation through absorption from the interstices. Generally, the insulation absorbs about 3 to about 30 weight percent cable filling compound or one or more of its hydrocarbon constituents, in total, based on the weight of polyolefin insulation. A typical absorption is in the range of about 5 to about 25 weight percent based on the weight of polyolefin. Cable filling compound generally contains hydrocarbons of varying molecular weights. The absorption of cable filling compound into the polyolefin insulation, or swelling, is preferential for the lower molecular weight constituents of the cable filling compound. This swelling of the polyolefin insulation results in migration of additives from the insulation to the cable filler compound as discussed supra. The presence of the cable filling compound therefore presents an additional obstacle towards stabilizing polyolefin insulation.

Examples of hydrocarbon cable filler grease (cable filling compound) are petrolatum; petrolatum/polyolefin wax mixtures; oil modified thermoplastic rubber (ETPR or extended thermoplastic rubber); paraffin oil; naphthenic oil; mineral oil; the aforementioned oils thickened with a residual oil, petrolatum, or wax; polyethylene wax; mineral oil/rubber block copolymer mixture; lubricating grease; and various mixtures thereof, all of which meet industrial requirements similar to those described above.

In addition to resisting extraction of the antioxidants, the stabilized polyolefin wire insulation formulation must be able to withstand any destabilizing effect absorbed constituents from the cable filler compound might have. Further, the stabilization package must mediate against the copper wire conductor, which is a potential catalyst for polyolefin oxidative degradation, and it must also counter the effect of residuals of chemical blowing agents present in cellular and cellular/solid (foam/skin) polymeric foamed insulation.

In addition to components (b) and (c), the insulation of the cable construction of this invention may comprise further costabilizers (additives) such as for example, the following:

1. Antioxidants

1.1. <u>Alkylated monophenols</u>, for example 2,6-di-tert-butyl-4-methylphenol, 2-tert-butyl-4,6-dimethylphenol, 2,6-di-tert-butyl-4-ethylphenol, 2,6-di-tert-butyl-4-n-butylphenol, 2,6-di-tert-butyl-4-isobutylphenol, 2,6-dicyclopentyl-4-methylphenol, 2-(a-methylcyclohexyl)-

- 4,6-dimethylphenol, 2,6-dioctadecyl-4-methylphenol, 2,4,6-tricyclohexylphenol, 2,6-di-tert-butyl-4-methoxymethylphenol, nonylphenols which are linear or branched in the side chains, for example, 2,6-di-nonyl-4-methylphenol, 2,4-dimethyl-6-(1-methylundec-1-yl)phenol, 2,4-dimethyl-6-(1-methylheptadec-1-yl)phenol, 2,4-dimethyl-6-(1-methyltridec-1-yl)phenol and mixtures thereof.
- 1.2. <u>Alkylthiomethylphenols</u>, for example 2,4-dioctylthiomethyl-6-tert-butylphenol, 2,4-dioctylthiomethyl-6-methylphenol, 2,4-dioctylthiomethyl-6-ethylphenol, 2,6-di-dodecylthiomethyl-4-nonylphenol.
- 1.3. <u>Hydroquinones and alkylated hydroquinones</u>, for example 2,6-di-tert-butyl-4-methoxyphenol, 2,5-di-tert-butylhydroquinone, 2,5-di-tert-amylhydroquinone, 2,6-diphenyl-4-octadecyloxyphenol, 2,6-di-tert-butylhydroquinone, 2,5-di-tert-butyl-4-hydroxyanisole, 3,5-di-tert-butyl-4-hydroxyphenyl stearate, bis-(3,5-di-tert-butyl-4-hydroxyphenyl) adipate.
- 1.4. <u>Tocopherols</u>, for example a-tocopherol, b-tocopherol, g-tocopherol, d-tocopherol and mixtures thereof (Vitamin E).
- 1.5. <u>Hydroxylated thiodiphenyl ethers</u>, for example 2,2'-thiobis(6-tert-butyl-4-methylphenol), 2,2'-thiobis(4-octylphenol), 4,4'-thiobis(6-tert-butyl-3-methylphenol), 4,4'-thiobis(6-tert-butyl-2-methylphenol), 4,4'-thiobis-(3,6-di-sec-amylphenol), 4,4'-bis(2,6-dimethyl-4-hydroxyphenyl)disulfide.
- 1.6. <u>Alkylidenebisphenols</u>, for example 2,2'-methylenebis(6-tert-butyl-4-methylphenol), 2,2'-methylenebis(6-tert-butyl-4-ethylphenol), 2,2'-methylenebis[4-methyl-6-(a-methylcyclohexyl)phenol], 2,2'-methylenebis(4-methyl-6-cyclohexylphenol), 2,2'-methylenebis(6-nonyl-4-methylphenol), 2,2'-methylenebis(4,6-di-tert-butylphenol), 2,2'-ethylidenebis(6-tert-butyl-4-isobutylphenol), 2,2'-methylenebis(6-(a,a-dimethylbenzyl)-4-nonylphenol], 2,2'-methylenebis[6-(a,a-dimethylbenzyl)-4-nonylphenol], 4,4'-methylenebis(2,6-di-tert-butylphenol), 4,4'-methylenebis(6-tert-butyl-2-methylphenol), 1,1-bis(5-tert-butyl-4-hydroxy-2-methylphenyl)butane, 2,6-bis(3-tert-butyl-5-methyl-2-hydroxybenzyl)-4-methylphenol, 1,1,3-tris(5-tert-butyl-4-hydroxy-2-methyl-phenyl)-3-n-

dodecylmercaptobutane, ethylene glycol bis[3,3-bis(3-tert-butyl-4-hydroxyphenyl)butyrate], bis(3-tert-butyl-4-hydroxy-5-methyl-phenyl)dicyclopentadiene, bis[2-(3'tert-butyl-2-hydroxy-5-methylbenzyl)-6-tert-butyl-4-methylphenyl]terephthalate, 1,1-bis-(3,5-dimethyl-2-hydroxyphenyl)butane, 2,2-bis-(3,5-di-tert-butyl-4-hydroxyphenyl)propane, 2,2-bis-(5-tert-butyl-4-hydroxy2-methylphenyl)-4-n-dodecylmercaptobutane, 1,1,5,5-tetra-(5-tert-butyl-4-hydroxy-2-methylphenyl)pentane.

- 1.7. O-, N- and S-benzyl compounds, for example 3,5,3',5'-tetra-tert-butyl-4,4'-dihydroxydibenzyl ether, octadecyl-4-hydroxy-3,5-dimethylbenzylmercaptoacetate, tridecyl-4-hydroxy-3,5-di-tert-butyl-4-hydroxybenzyl)amine, bis(4-tert-butyl-3-hydroxy-2,6-dimethylbenzyl)dithioterephthalate, bis(3,5-di-tert-butyl-4-hydroxybenzyl)sulfide, isooctyl-3,5-di-tert-butyl-4-hydroxybenzylmercaptoacetate.
- 1.8. <u>Hydroxybenzylated malonates</u>, for example dioctadecyl-2,2-bis-(3,5-di-tert-butyl-2-hydroxybenzyl)-malonate, di-octadecyl-2-(3-tert-butyl-4-hydroxy-5-methylbenzyl)-malonate, di-dodecylmercaptoethyl-2,2-bis-(3,5-di-tert-butyl-4-hydroxybenzyl)malonate, bis[4-(1,1,3,3-tetramethylbutyl)phenyl]-2,2-bis(3,5-di-tert-butyl-4-hydroxybenzyl)malonate.
- 1.9. <u>Aromatic hydroxybenzyl compounds</u>, for example 1,3,5-tris-(3,5-di-tert-butyl-4-hydroxybenzyl)-2,4,6-trimethylbenzene, 1,4-bis(3,5-di-tert-butyl-4-hydroxybenzyl)-2,3,5,6-tetramethylbenzene, 2,4,6-tris(3,5-di-tert-butyl-4-hydroxybenzyl)phenol.
- 1.10. <u>Triazine compounds</u>, for example 2,4-bis(octylmercapto)-6-(3,5-di-tert-butyl-4-hydroxyanilino)-1,3,5-triazine, 2-octylmercapto-4,6-bis(3,5-di-tert-butyl-4-hydroxyanilino)-1,3,5-triazine, 2-octylmercapto-4,6-bis(3,5-di-tert-butyl-4-hydroxyphenoxy)-1,3,5-triazine, 2,4,6-tris(3,5-di-tert-butyl-4-hydroxyphenoxy)-1,2,3-triazine, 1,3,5-tris(3,5-di-tert-butyl-4-hydroxyphenoxyl) isocyanurate, 1,3,5-tris(4-tert-butyl-3-hydroxy-2,6-dimethylbenzyl) isocyanurate, 2,4,6-tris(3,5-di-tert-butyl-4-hydroxyphenylethyl)-1,3,5-triazine, 1,3,5-tris(3,5-di-tert-butyl-4-hydroxyphenylpropionyl)-hexahydro-1,3,5-triazine, 1,3,5-tris(3,5-dicyclohexyl-4-hydroxybenzyl) isocyanurate.
- 1.11. <u>Benzylphosphonates</u>, for example dimethyl-2,5-di-tert-butyl-4-hydroxybenzylphosphonate, diethyl-3,5-di-tert-butyl-4-hydroxybenzylphosphonate, dioctadecyl3,5-di-tert-butyl-4-hydroxybenzylphosphonate, dioctadecyl-5-tert-butyl-4-hydroxybenzylphosphonate,

- 12 -

3-methylbenzylphosphonate, the calcium salt of the monoethyl ester of 3,5-di-tert-butyl-4-

hydroxybenzylphosphonic acid.

- 1.12. <u>Acylaminophenols</u>, for example 4-hydroxylauranilide, 4-hydroxystearanilide, octyl N-(3,5-di-tert-butyl-4-hydroxyphenyl)carbamate.
- 1.13. Esters of b-(3,5-di-tert-butyl-4-hydroxyphenyl)propionic acid with mono- or polyhydric alcohols, e.g. with methanol, ethanol, n-octanol, i-octanol, octadecanol, 1,6-hexanediol, 1,9-nonanediol, ethylene glycol, 1,2-propanediol, neopentyl glycol, thiodiethylene glycol, diethylene glycol, triethylene glycol, pentaerythritol, tris(hydroxyethyl) isocyanurate, N,N'-bis(hydroxyethyl)oxamide, 3-thiaundecanol, 3-thiapentadecanol, trimethylhexanediol, trimethylolpropane, 4-hydroxymethyl-1-phospha-2,6,7-trioxabicyclo[2.2.2]octane.
- 1.14. Esters of b-(5-tert-butyl-4-hydroxy-3-methylphenyl)propionic acid with monoor polyhydric alcohols, e.g. with methanol, ethanol, n-octanol, i-octanol, octadecanol, 1,6-hexanediol, 1,9-nonanediol, ethylene glycol, 1,2-propanediol, neopentyl glycol, thiodiethylene glycol, diethylene glycol, triethylene glycol, pentaerythritol, tris(hydroxyethyl) isocyanurate, N,N'-bis(hydroxyethyl)oxamide, 3-thiaundecanol, 3-thiapentadecanol, trimethylhexanediol, trimethylolpropane, 4-hydroxymethyl-1-phospha-2,6,7-trioxabicyclo[2.2.2]octane.
- 1.15. Esters of b-(3,5-dicyclohexyl-4-hydroxyphenyl)propionic acid with mono- or polyhydric alcohols, e.g. with methanol, ethanol, octanol, octadecanol, 1,6-hexanediol, 1,9-nonanediol, ethylene glycol, 1,2-propanediol, neopentyl glycol, thiodiethylene glycol, diethylene glycol, triethylene glycol, pentaerythritol, tris(hydroxyethyl) isocyanurate, N,N'-bis(hydroxyethyl)oxamide, 3-thiaundecanol, 3-thiapentadecanol, trimethylhexanediol, trimethylolpropane, 4-hydroxymethyl-1-phospha-2,6,7-trioxabicyclo[2,2,2]octane.
- 1.16. Esters of 3,5-di-tert-butyl-4-hydroxyphenyl acetic acid with mono- or polyhydric alcohols, e.g. with methanol, ethanol, octanol, octadecanol, 1,6-hexanediol, 1,9-nonanediol, ethylene glycol, 1,2-propanediol, neopentyl glycol, thiodiethylene glycol, diethylene glycol, triethylene glycol, pentaerythritol, tris(hydroxyethyl) isocyanurate, N,N'-bis(hydroxyethyl)oxamide, 3-thiaundecanol, 3-thiapentadecanol, trimethylhexanediol, trimethylolpropane, 4-hydroxymethyl-1-phospha-2,6,7-trioxabicyclo[2.2.2]octane.

1.17. Amides of b-(3,5-di-tert-butyl-4-hydroxyphenyl)propionic acid e.g. N,N'-bis(3,5-di-tert-butyl-4-hydroxyphenylpropionyl)hexamethylenediamide, N,N'-bis(3,5-di-tert-butyl-4-hydroxyphenylpropionyl)trimethylenediamide, N,N'-bis(3,5-di-tert-butyl-4-hydroxyphenylpropionyl)hydrazide, N,N'-bis[2-(3-[3,5-di-tert-butyl-4-hydroxyphenyl]propionyloxy)ethyl]oxamide (Naugard®XL-1 supplied by Uniroyal).

1.18. Ascorbic acid (vitamin C)

1.19. Aminic antioxidants, for example N,N'-di-isopropyl-p-phenylenediamine, N,N'di-sec-butyl-p-phenylenediamine, N,N'-bis(1,4-dimethylpentyl)-p-phenylenediamine, N,N'bis(1-ethyl-3-methylpentyl)-p-phenylenediamine, N,N'-bis(1-methylheptyl)-pphenylenediamine, N,N'-dicyclohexyl-p-phenylenediamine, N,N'-diphenyl-pphenylenediamine, N,N'-bis(2-naphthyl)-p-phenylenediamine, N-isopropyl-N'-phenyl-pphenylenediamine, N-(1,3-dimethylbutyl)-N'-phenyl-p-phenylenediamine, N-(1-methylheptyl)-N'-phenyl-p-phenylenediamine, N-cyclohexyl-N'-phenyl-p-phenlenediamine, 4-(ptoluenesulfamoyl)diphenylamine, N,N'-dimethyl-N,N'-di-sec-butyl-p-phenylenediamine, diphenylamine, N-allyldiphenylamine, 4-isopropoxydiphenylamine, N-phenyl-1naphthylamine, N-(4-tert-octylphenyl)-1-naphthylamine, N-phenyl-2-naphthylamine, octylated diphenylamine, for example p,p'-di-tert-octyldiphenylamine, 4-n-butylaminophenol, 4-butyrylaminophenol, 4-nonanoylaminophenol, 4-dodecanoylaminophenol, 4-octadecanoylaminophenol, bis(4-methoxyphenyl)amine, 2,6-di-tert-butyl-4dimethylaminomethylphenol, 2,4'-diaminodiphenylmethane, 4,4'-diaminodiphenylmethane, N,N,N',N'-tetramethyl-4,4'-diaminodiphenylmethane, 1,2-bis[(2-methylphenyl)amino]ethane, 1,2-bis(phenylamino)propane, (o-tolyl)biguanide, bis[4-(1',3'-dimethylbutyl)phenyl]amine, tertoctylated N-phenyl-1-naphthylamine, a mixture of mono- and dialkylated tert-butyl/tert-octyldiphenylamines, a mixture of mono- and dialkylated nonyldiphenylamines, a mixture of mono- and dialkylated dodecyldiphenylamines, a mixture of mono- and dialkylated isopropyl/isohexyldiphenylamines, a mixture of mono- and dialkylated tertbutyldiphenylamines, 2,3-dihydro-3,3-dimethyl-4H-1,4-benzothiazine, phenothiazine, a mixture of mono- and dialkylated tert-butyl/tert-octylphenothiazines, a mixture of mono- and dialkylated tert-octyl-phenothiazines, N-allylphenothiazin, N,N,N',N'-tetraphenyl-1,4diaminobut-2-ene, N,N-bis(2,2,6,6-tetramethyl-piperid-4-yl-hexamethylenediamine, bis(2,2,6,6-tetramethylpiperid-4-yl)sebacate, 2,2,6,6-tetramethylpiperidin-4-one, 2,2,6,6tetramethylpiperidin-4-ol.

2. UV absorbers and light stabilizers

- 2.1. 2-(2-Hydroxyphenyl)benzotriazoles, for example 2-(2-hydroxy-5methylphenyl)-benzotriazole, 2-(3,5-di-tert-butyl-2-hydroxyphenyl)benzotriazole, 2-(5-tertbutyl-2-hydroxyphenyl)benzotriazole, 2-(2-hydroxy-5-(1,1,3,3tetramethylbutyl)phenyl)benzotriazole, 2-(3,5-di-tert-butyl-2-hydroxyphenyl)-5-chloro-benzotriazole, 2-(3-tert-butyl- 2-hydroxy-5methylphenyl)-5-chloro-benzotriazole, 2-(3-sec-butyl-5-tert-butyl-2hydroxyphenyl)benzotriazole, 2-(2-hydroxy-4-octyloxyphenyl)benzotriazole, 2-(3,5-di-tertamyl-2-hydroxyphenyl)benzotriazole, 2-(3,5-bis-(a,a-dimethylbenzyl)-2hydroxyphenyl)benzotriazole, 2-(3-tert-butyl-2-hydroxy-5-(2-octyloxycarbonylethyl)phenyl)-5chloro-benzotriazole, 2-(3-tert-butyl-5-[2-(2-ethylhexyloxy)-carbonylethyl]-2-hydroxyphenyl)-5-chloro-benzotriazole, 2-(3-tert-butyl-2-hydroxy-5-(2-methoxycarbonylethyl)phenyl)-5-chlorobenzotriazole, 2-(3-tert-butyl-2-hydroxy-5-(2-methoxycarbonylethyl)phenyl)benzotriazole, 2-(3-tert-butyl-2-hydroxy-5-(2-octyloxycarbonylethyl)phenyl)benzotriazole, 2-(3-tert-butyl-5-[2-(2-ethylhexyloxy)carbonylethyl]-2-hydroxyphenyl)benzotriazole, 2-(3-dodecyl-2-hydroxy-5methylphenyl)benzotriazole, 2-(3-tert-butyl-2-hydroxy-5-(2isooctyloxycarbonylethyl)phenylbenzotriazole, 2,2'-methylene-bis[4-(1,1,3,3tetramethylbutyl)-6-benzotriazole-2-ylphenol]; the transesterification product of 2-[3-tertbutyl-5-(2-methoxycarbonylethyl)-2-hydroxyphenyl]-2H-benzotriazole with polyethylene glycol 300; $\left[R-CH_2CH_2-COO-CH_2CH_2\right]_2$ where R = 3'-tert-butyl-4'-hydroxy-5'-2H-benzotriazol-2-ylphenyl, 2-[2-hydroxy-3-(a,a-dimethylbenzyl)-5-(1,1,3,3-tetramethylbutyl)-phenyl]benzotriazole; 2-[2-hydroxy-3-(1,1,3,3-tetramethylbutyl)-5-(a,a-dimethylbenzyl)-phenyl]benzotriazole.
- 2.2. <u>2-Hydroxybenzophenones</u>, for example the 4-hydroxy, 4-methoxy, 4-octyloxy, 4-decyloxy, 4-dodecyloxy, 4-benzyloxy, 4,2',4'-trihydroxy and 2'-hydroxy-4,4'-dimethoxy derivatives.
- 2.3. Esters of substituted and unsubstituted benzoic acids, as for example 4-tertbutyl-phenyl salicylate, phenyl salicylate, octylphenyl salicylate, dibenzoyl resorcinol, bis(4-tert-butylbenzoyl) resorcinol, benzoyl resorcinol, 2,4-di-tert-butylphenyl 3,5-di-tert-butyl-

WO 00/58975 PCT/EP00/01403

- 15 -

4-hydroxybenzoate, hexadecyl 3,5-di-tert-butyl-4-hydroxybenzoate, octadecyl 3,5-di-tert-butyl-4-hydroxybenzoate, 2-methyl-4,6-di-tert-butylphenyl 3,5-di-tert-butyl-4-hydroxybenzoate.

- 2.4. <u>Acrylates</u>, for example ethyl a-cyano-b,b-diphenylacrylate, isooctyl a-cyano-b,b-diphenylacrylate, methyl a-carbomethoxycinnamate, methyl a-cyano-b-methyl-p-methoxy-cinnamate, butyl a-cyano-b-methyl-p-methoxy-cinnamate, methyl a-carbomethoxy-p-methoxycinnamate and N-(b-carbomethoxy-b-cyanovinyl)-2-methylindoline.
- 2.5. Nickel compounds, for example nickel complexes of 2,2'-thio-bis-[4-(1,1,3,3-tetramethylbutyl)phenol], such as the 1:1 or 1:2 complex, with or without additional ligands such as n-butylamine, triethanolamine or N-cyclohexyldiethanolamine, nickel dibutyldithiocarbamate, nickel salts of the monoalkyl esters, e.g. the methyl or ethyl ester, of 4-hydroxy-3,5-di-tert-butylbenzylphosphonic acid, nickel complexes of ketoximes, e.g. of 2-hydroxy-4-methylphenyl undecylketoxime, nickel complexes of 1-phenyl-4-lauroyl-5-hydroxypyrazole, with or without additional ligands.
- 2.6. Sterically hindered amines, for example bis(2,2,6,6-tetramethyl-4piperidyl)sebacate, bis(2,2,6,6-tetramethyl-4-piperidyl)succinate, bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate, bis(1-octyloxy-2,2,6,6-tetramethyl-4-piperidyl)sebacate, bis(1,2,2,6,6pentamethyl-4-piperidyl) n-butyl-3,5-di-tert-butyl-4-hydroxybenzylmalonate, the condensate of 1-(2-hydroxyethyl)-2,2,6,6-tetramethyl-4-hydroxypiperidine and succinic acid, linear or cyclic condensates of N,N'-bis(2,2,6,6-tetramethyl-4-piperidyl)hexamethylenediamine and 4tert-octylamino-2,6-dichloro-1,3,5-triazine, tris(2,2,6,6-tetramethyl-4-piperidyl)nitrilotriacetate, tetrakis(2,2,6,6-tetramethyl-4-piperidyl)-1,2,3,4-butane-tetracarboxylate, 1,1'-(1,2ethanediyl)-bis(3,3,5,5-tetramethylpiperazinone), 4-benzoyl-2,2,6,6-tetramethylpiperidine, 4stearyloxy-2,2,6,6-tetramethylpiperidine, bis(1,2,2,6,6-pentamethylpiperidyl)-2-n-butyl-2-(2hydroxy-3,5-di-tert-butylbenzyl)malonate, 3-n-octyl-7,7,9,9-tetramethyl-1,3,8triazaspiro[4.5]decan-2,4-dione, bis(1-octyloxy-2,2,6,6-tetramethylpiperidyl)sebacate, bis(1octyloxy-2,2,6,6-tetramethylpiperidyl)succinate, linear or cyclic condensates of N,N'-bis-(2,2,6,6-tetramethyl-4-piperidyl)hexamethylenediamine and 4-morpholino-2,6-dichloro-1,3,5triazine, the condensate of 2-chloro-4,6-bis(4-n-butylamino-2,2,6,6-tetramethylpiperidyl)-1,3,5-triazine and 1,2-bis(3-aminopropylamino)ethane, the condensate of 2-chloro-4,6-di-(4n-butylamino-1,2,2,6,6-pentamethylpiperidyl)-1,3,5-triazine and 1,2-bis-(3-

aminopropylamino)ethane, 8-acetyl-3-dodecyl-7,7,9,9-tetramethyl-1,3,8triazaspiro[4.5]decane-2,4-dione, 3-dodecyl-1-(2,2,6,6-tetramethyl-4-piperidyl)pyrrolidin-2,5dione, 3-dodecyl-1-(1,2,2,6,6-pentamethyl-4-piperidyl)pyrrolidine-2,5-dione, a mixture of 4hexadecyloxy- and 4-stearyloxy-2,2,6,6-tetramethylpiperidine, a condensation product of N,N'-bis(2,2,6,6-tetramethyl-4-piperidyl)hexamethylenediamine and 4-cyclohexylamino-2,6dichloro-1,3,5-triazine, a condensation product of 1,2-bis(3-aminopropylamino)ethane and 2,4,6-trichloro-1,3,5-triazine as well as 4-butylamino-2,2,6,6-tetramethylpiperidine (CAS Reg. No. [136504-96-6]); N-(2,2,6,6-tetramethyl-4-piperidyl)-n-dodecylsuccinimid, N-(1,2,2,6,6pentamethyl-4-piperidyl)-n-dodecylsuccinimid, 2-undecyl-7,7,9,9-tetramethyl-1-oxa-3,8diaza-4-oxo-spiro[4,5]decane, a reaction product of 7,7,9,9-tetramethyl-2-cycloundecyl-1oxa-3,8-diaza-4-oxospiro [4,5]decane and epichlorohydrin, 1,1-bis(1,2,2,6,6-pentamethyl-4piperidyloxycarbonyl)-2-(4-methoxyphenyl)ethene, N,N'-bis-formyl-N,N'-bis(2,2,6,6tetramethyl-4-piperidyl)hexamethylenediamine, diester of 4-methoxy-methylene-malonic acid with 1,2,2,6,6-pentamethyl-4-hydroxypiperidine, poly[methylpropyl-3-oxy-4-(2,2,6,6tetramethyl-4-piperidyl)]siloxane, reaction product of maleic acid anhydride-a-olefincopolymer with 2,2,6,6-tetramethyl-4-aminopiperidine or 1,2,2,6,6-pentamethyl-4aminopiperidine.

- 2.7. Oxamides, for example 4,4'-dioctyloxyoxanilide, 2,2'-diethoxyoxanilide, 2,2'-dioctyloxy-5,5'-di-tert-butoxanilide, 2,2'-didodecyloxy-5,5'-di-tert-butoxanilide, 2-ethoxy-2'-ethyloxanilide, N,N'-bis(3-dimethylaminopropyl)oxamide, 2-ethoxy-5-tert-butyl-2'-ethoxanilide and its mixture with 2-ethoxy-2'-ethyl-5,4'-di-tert-butoxanilide, mixtures of o- and p-methoxy-disubstituted oxanilides and mixtures of o- and p-ethoxy-disubstituted oxanilides.
- 2.8. <u>2-(2-Hydroxyphenyl)-1,3,5-triazines</u>, for example 2,4,6-tris(2-hydroxy-4-octyloxyphenyl)-1,3,5-triazine, 2-(2-hydroxy-4-octyloxyphenyl)-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2,4-bis(2-hydroxy-4-propyloxyphenyl)-6-(2,4-dimethylphenyl)-1,3,5-triazine, 2-(2-hydroxy-4-octyloxyphenyl)-4,6-bis(4-methylphenyl)-1,3,5-triazine, 2-(2-hydroxy-4-dodecyloxyphenyl)-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-(2-hydroxy-4-tridecyloxyphenyl)-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-[2-hydroxy-4-(2-hydroxy-3-butyloxypropoxy)phenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-[2-hydroxy-4-(2-hydroxy-3-octyloxy-propyloxy)phenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-[4-(dodecyloxy/tridecyloxy-2-hydroxy-phenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-[2-hydroxy-4-dimethylphenyl)-1,3,5-triazine, 2-[2-hydroxy-2-hydroxy-phenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-[2-hydroxy-2-hydro

- 4-(2-hydroxy-3-dodecyloxy-propoxy)phenyl]-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 2-(2-hydroxy-4-hexyloxy)phenyl-4,6-diphenyl-1,3,5-triazine, 2-(2-hydroxy-4-methoxyphenyl)-4,6-diphenyl-1,3,5-triazine, 2,4,6-tris[2-hydroxy-4-(3-butoxy-2-hydroxypropoxy)phenyl]-1,3,5-triazine, 2-(2-hydroxyphenyl)-4-(4-methoxyphenyl)-6-phenyl-1,3,5-triazine, 2-{2-hydroxy-4-[3-(2-ethylhexyl-1-oxy)-2-hydroxypropyloxy]phenyl}-4,6-bis(2,4-dimethylphenyl)-1,3,5-triazine, 4,6-bis(2,4-dimethylphenyl)-2-[2-hydroxy-4-(2-hydroxy-3-nonyloxypropoxy)-5-(1-methyl-1-phenylethyl)phenyl]-1,3,5-triazine.
- 3. <u>Metal deactivators</u>, for example N,N'-diphenyloxamide, N-salicylal-N'-salicyloyl hydrazine, N,N'-bis(salicyloyl) hydrazine, N,N'-bis(3,5-di-tert-butyl-4-hydroxyphenylpropionyl) hydrazine, 3-salicyloylamino-1,2,4-triazole, bis(benzylidene)oxalyl dihydrazide, oxanilide, isophthaloyl dihydrazide, sebacoyl bisphenylhydrazide, N,N'-diacetyladipoyl dihydrazide, N,N'-bis(salicyloyl)oxalyl dihydrazide, N,N'-bis(salicyloyl)thiopropionyl dihydrazide.
- 4. Phosphites and phosphonites, for example triphenyl phosphite, diphenyl alkyl phosphites, phenyl dialkyl phosphites, tris(nonylphenyl) phosphite, trilauryl phosphite, trioctadecyl phosphite, distearyl pentaerythritol diphosphite, tris(2,4-di-tert-butylphenyl) phosphite, diisodecyl pentaerythritol diphosphite, bis(2,4-di-tert-butylphenyl) pentaerythritol diphosphite, bis(2,6-di-tert-butyl-4-methylphenyl)-pentaerythritol diphosphite, diisodecyloxypentaerythritol diphosphite, bis(2,4-di-tert-butyl-6-methylphenyl)pentaerythritol diphosphite, tristearyl sorbitol diphosphite, bis(2,4-6-tris(tert-butylphenyl)pentaerythritol diphosphite, tristearyl sorbitol triphosphite, tetrakis(2,4-di-tert-butylphenyl) 4,4'-biphenylene diphosphonite, 6-isooctyloxy-2,4,8,10-tetra-tert-butyl-dibenzo[d,f][1,3,2]dioxaphosphepin, 6-fluoro-2,4,8,10-tetra-tert-butyl-12-methyl-dibenzo[d,g][1,3,2]dioxaphosphocin, bis(2,4-di-tert-butyl-6-methylphenyl) methyl phosphite, bis(2,4-di-tert-butyl-6-methylphenyl) ethyl phosphite, 2,2',2"-nitrilo[triethyltris(3,3',5,5'-tetra-tert-butyl-1,1'-biphenyl-2,2'-diyl)phosphite.

Especially preferred are the following phosphites:

Tris(2,4-di-tert-butylphenyl) phosphite (Irgafos®168, Ciba Specialty Chemicals Corp.), tris(nonylphenyl) phosphite,

$$(CH_3)_3C \longrightarrow C(CH_3)_3 \qquad (CH_3)_3C \longrightarrow C(CH_3)_3C \longrightarrow C(CH_3)_3 \qquad (CH_3)_3C \longrightarrow C(CH_3)_3C \longrightarrow C($$

$$(CH_3)_3C$$
 $C(CH_3)_3$
 C
 $C(CH_3)_3$
 C
 $C(CH_3)_3$
 C
 $C(CH_3)_3$
 C
 $C(CH_3)_3$
 C
 $C(CH_3)_3$

$$H_3C$$
 $C(CH_3)_3$ C $C(CH_3)_3$ C

(F)
$$H_{37}C_{18} O - P'_{O} O - C_{18}H_{37}$$

$$H_{3}C - C - CH_{3}$$

$$H_{3}C - C - CH_{3}$$

$$CH_{3} C - CH_{3}$$

PCT/EP00/01403

- 5. <u>Hydroxylamines</u>, for example N,N-dibenzylhydroxylamine, N,N-diethylhydroxylamine, N,N-dioctylhydroxylamine, N,N-dilaurylhydroxylamine, N,N-ditetradecylhydroxylamine, N,N-dihexadecylhydroxylamine, N,N-dioctadecylhydroxylamine, N-hexadecyl-N-octadecylhydroxylamine, N,N-dialkylhydroxylamine derived from hydrogenated tallow amine, N,N-di(alkyl)hydroxylamine produced by the direct oxidation of N,N-di(hydrogenated tallow)amine.
- 6. <u>Nitrones</u>, for example N-benzyl-alpha-phenyl-nitrone, N-ethyl-alpha-methyl-nitrone, N-octyl-alpha-heptyl-nitrone, N-lauryl-alpha-undecyl-nitrone, N-tetradecyl-alpha-tridcyl-nitrone, N-hexadecyl-alpha-pentadecyl-nitrone, N-octadecyl-alpha-heptadecyl-nitrone, N-hexadecyl-nitrone, N-ocatadecyl-alpha-pentadecyl-nitrone, N-heptadecyl-alpha-heptadecyl-nitrone, N-octadecyl-alpha-hexadecyl-nitrone, nitrone derived from N,N-dialkylhydroxylamine derived from hydrogenated tallow amine.
- 7. Benzofuranones and indolinones, for example those disclosed in U.S. 4,325,863; U.S. 4,338,244; U.S. 5,175,312; U.S. 5,216,052; U.S. 5,252,643; DE-A-4316611; DE-A-4316622; DE-A-4316876; EP-A-0589839 or EP-A-0591102 or 3-[4-(2-acetoxyethoxy)-phenyl]-5,7-di-tert-butyl-benzofuran-2-one, 5,7-di-tert-butyl-3-[4-(2-stearoyloxyethoxy)phenyl]benzofuran-2-one, 3,3'-bis[5,7-di-tert-butyl-3-(4-[2-hydroxyethoxy]phenyl)benzofuran-2-one], 5,7-di-tert-butyl-3-(4-ethoxyphenyl)benzofuran-2-one, 3-(4-acetoxy-3,5-dimethylphenyl)-5,7-di-tert-butyl-benzofuran-2-one, 3-(3,5-dimethyl-4-pivaloyloxyphenyl)-5,7-di-tert-butyl-benzofuran-2-one, 3-(2,3-dimethylphenyl)-5,7-di-tert-butyl-benzofuran-2-one, 3-(2,3-dimethylphenyl)-5,7-di-tert-butyl-benzofuran-2-one.
 - 8. Thiosynergists, for example dilauryl thiodipropionate or distearyl thiodipropionate.
- 9. <u>Peroxide scavengers</u>, for example esters of b-thiodipropionic acid, for example the lauryl, stearyl, myristyl or tridecyl esters, mercaptobenzimidazole or the zinc salt of 2-mercaptobenzimidazole, zinc dibutyldithiocarbamate, dioctadecyl disulfide, pentaerythritol tetrakis(b-dodecylmercapto)propionate.
- 10. <u>Polyamide stabilizers</u>, for example copper salts in combination with iodides and/or phosphorus compounds and salts of divalent manganese.

- 11. <u>Basic co-stabilizers</u>, for example melamine, polyvinylpyrrolidone, dicyandiamide, triallyl cyanurate, urea derivatives, hydrazine derivatives, amines, polyamides, polyurethanes, alkali metal salts and alkaline earth metal salts of higher fatty acids, for example, calcium stearate, zinc stearate, magnesium behenate, magnesium stearate, sodium ricinoleate and potassium palmitate, antimony pyrocatecholate or zinc pyrocatecholate.
- 12. <u>Nucleating agents</u>, for example inorganic substances such as talcum, metal oxides such as titanium dioxide or magnesium oxide, phosphates, carbonates or sulfates of, preferably, alkaline earth metals; organic compounds such as mono- or polycarboxylic acids and the salts thereof, e.g. 4-tert-butylbenzoic acid, adipic acid, diphenylacetic acid, sodium succinate or sodium benzoate; polymeric compounds such as ionic copolymers (ionomers).
- 13. <u>Fillers and reinforcing agents</u>, for example calcium carbonate, silicates, glass fibres, glass bulbs, asbestos, talc, kaolin, mica, barium sulfate, metal oxides and hydroxides, carbon black, graphite, wood flour and flours or fibers of other natural products, synthetic fibers.
- 14. Other additives, for example plasticizers, lubricants, emulsifiers, pigments, dyes, optical brighteners, rheology additives, catalysts, flow-control agents, slip agents, crosslinking agents, crosslinking boosters, halogen scavengers, smoke inhibitors, flameproofing agents, antistatic agents, clarifying agents and blowing agents.

The fillers (item 13. in the list) are for example metal hydroxides, especially magnesium hydroxide and aluminum hydroxide. They may be added in a concentration of about 0.01 to about 60 weight percent based on the weight of polyolefin.

Blowing agents (item 14. in the list), such as azodicarbonamide, can be used to provide foam rather than solid insulation.

The primary antioxidants of component (b), the metal deactivators of component (c) and optional further additives are incorporated into the polyolefin of component (a) by known methods, for example before or after molding or also by applying the dissolved or dispersed stabilizer mixture to the polyolefin, with or without subsequent evaporation of the solvent.

Components (b) and (c) and optional further additives can also be added to the polyolefin in the form of a masterbatch which contains these components in a concentration of, for example, about 2.5 percent to about 25 percent by weight.

The antioxidants of component (b), in total, are employed e.g. in the range of about 0.01 weight percent to about 1.5 weight percent based on the weight of the polyolefin (a). Preferably, the compounds of component (b), in total, are employed in the range from about 0.05 weight percent to about 1.0 weight percent based on the weight of the polyolefin (a).

The metal deactivators of component (c), in total, are employed e.g. in the range of about 0.1 weight percent to about 2.5 weight percent based on the weight of the polyolefin (a). Preferably, the compounds of component (c), in total, are employed in the range from about 0.1 weight percent to about 2.0 weight percent based on the weight of the polyolefin (a).

The weight ratio of the metal deactivators of component (c) to the antioxidants of component (b) employed in the instant invention is e.g. in the range of from about 0.5:1 to about 20:1. Preferably, the ratio of component (c) to component (b) is in the range of from about 1:1 to about 10:1.

The following Examples illustrate the invention in more detail. They are not meant to be construed as limiting the invention in any manner whatsoever.

Example 1: Stabilization of Polyolefins in Grease Filled Cable Construction

100 parts high density polyethylene are dry blended with 0.4 parts of Irganox® MD 1024 (1,2 -bis(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyl)hydrazine) and 0.2 parts of one of the primary antioxidants listed in Table 1 below. The mixtures are melt compounded into pellets at 230° C in a Superior/MPM extruder using a 24:1 L/D screw with Maddock mixing head at 60 rpm.

The pelletized polyethylene containing the stabilizer mixtures are compression molded at 204°C (400°F) into 0.254 mm (0.01 inch) thick films with Mylar backing. "Initial oxidation induction time" (OIT) is measured on these test films.

WO 00/58975 PCT/EP00/01403

- 22 -

The sample films are then submersed in Witcogel®, available from Witco, a typical hydrocarbon cable filler grease used in telecom cables. The Witco filling compound contains 0.6 % Irganox® 1035, thiodiethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate]. The sample films submersed in the filling compound are exposed in an air oven at 70° C for 14 days. The samples are then wiped clean of the cable filler grease. "Aged oxidation induction time" is measured on these samples.

OIT testing is accomplished using a differential scanning calorimeter as per ASTM standard test method D3895. The test conditions are: Uncrimped aluminum pan; no screen; heat up to 200° C under nitrogen, followed by a switch to a 100 milliliter/minute flow of oxygen. Oxidation induction time (OIT) is the time interval between the start of oxygen flow and the exothermic decomposition of the test specimen. OIT is reported in minutes; the longer the OIT the more effective the stabilizer mixture is at preventing oxidative degradation. Relative performance of stabilizer mixtures in grease filled cable applications can be predicted by comparing the initial OIT values and the aged OIT values.

Table 1

Primary Antioxidant	Initial OIT (minutes)	Aged OIT (minutes)
Irganox® 1010	77	25
Irganox® 1098	161	90
Irganox [®] 3114	91	44
Irganox® 3125	126	51

The stabilizer mixtures of Irganox® 1098, Irganox® 3114, Irganox® 3125, each with the metal deactivator Irganox® MD 1024 (1,2 -bis(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyl)hydrazine) outperform a state of the art stabilizer mixture of Irganox® 1010/Irganox® MD 1024 in initial and aged OIT. Irganox® 1098 is N,N'-hexane-1,6-diylbis-(3-(3,5-di-tert-butyl-4-hydroxyphenylpropionamide)), Irganox® 3114 is tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate, Irganox® 3125 is tris(2-(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyloxy)ethyl) isocyanurate. Irganox® is a trademark of Ciba Specialty Chemicals Corporation.

What is claimed is:

- 1. A stabilized cable construction, which comprises
- (i) a plurality of insulated electrical conductors having interstices therebetween, said insulation comprising
 - (a) one or more polyolefins, and
- (b) one or more primary antioxidants selected from the group of N,N'-hexane-1,6-diylbis-(3-(3,5-di-tert-butyl-4-hydroxyphenylpropionamide)), tris(3,5-di-tert-butyl-4-hydroxybenzyl) isocyanurate and tris(2-(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyloxy)ethyl) isocyanurate, and
- (c) one or more metal deactivators selected from the alkylhydroxyphenylalkanoyl hydrazines, and
 - (ii) hydrocarbon cable filler grease within the interstices, and
 - (iii) a sheath surrounding components (i) and (ii).
- 2. A cable construction according to claim 1 wherein said polyolefins of component (a) are polyethylene or polypropylene or mixtures thereof.
- 3. A cable construction according to claim 1 in which the metal deactivators of component (c) are of the formula

$$R_1$$
 O
 N
 R_3
 HO
 R_2

wherein n is 0 or an integer from 1 to 5;

R₁ is a straight or branched chain alkyl having 1 to 6 carbon atoms;

R₂ is hydrogen or R₁; and

R₃ is hydrogen, an alkanoyl having 2 to 18 carbon atoms, or a group of the formula

$$R_1$$
 O $CH_2)_n$ R_2

wherein n, R_1 and R_2 independently have the same definitions as above.

- 4. A cable construction according to claim 1 in which the metal deactivator of component (c) is 1,2 -bis(3,5-di-tert-butyl-4-hydroxyhydrocinnamoyl)hydrazine.
- 5. A cable construction according to claim 1 in which said antioxidants of component (b), in total, are present in the range from about 0.05 weight percent to about 1.0 weight percent based on the weight of the polyolefin of component (a).

WO 00/58975 PCT/EP00/01403

- 26 -

- 6. A cable construction according to claim 1 in which said metal deactivators of component (c), in total, are present in the range from about 0.1 weight percent to about 2.0 weight percent based on the weight of the polyolefin of component (a).
- 7. A cable construction according to claim 1 in which the hydrocarbon cable filler grease of component (ii) or one or more of the hydrocarbon constituents thereof is present in the polyolefin of component (a).
- 8. A cable construction according to claim 1 in which the hydrocarbon cable filler grease of component (ii) or one or more of the hydrocarbon constituents thereof, in total, is present in the polyolefin of component (a) in the range of about 3 to about 30 weight percent based on the weight of component (a).

INTERNATIONAL SEARCH REPORT

Interr nal Application No

		! '	01/11 00/01403
A. CLASSII IPC 7	FICATION OF SUBJECT MATTER H01B3/44		
According to	o International Patent Classification (IPC) or to both national classific	cation and IPC	
	SEARCHED		
IPC 7	cumentation searched (classification system followed by classificat H01B		
	ion searched other than minimum documentation to the extent that		
Electronic d	ata base consulted during the international search (name of data ba	ase and, where practical, se	earch terms used)
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the re	levant passages	Relevant to claim No.
Υ	US 4 233 470 A (WIGHT JR FREDERI 11 November 1980 (1980-11-11) column 8, line 59 - line 69 tables IV,VIII	CK R)	1-8
Υ	GB 1 439 009 A (UNION CARBIDE CO 9 June 1976 (1976-06-09) page 6, Table	RP)	1-8
Υ	WO 93 24935 A (UNION CARBIDE CHE 9 December 1993 (1993-12-09) cited in the application example 18	M PLASTIC)	1-8
Υ	WO 93 24938 A (UNION CARBIDE CHE 9 December 1993 (1993-12-09) cited in the application example 3	M PLASTIC)	1-8
		/	
X Furth	her documents are listed in the continuation of box C.	X Patent family mer	mbers are listed in annex.
"A" docume	tegories of cited documents : ent defining the general state of the art which is not lered to be of particular relevance	or priority date and no	ed after the international filing date of in conflict with the application but e principle or theory underlying the
"L" docume which	document but published on or after the international late at the international late on which may throw doubts on priority claim(s) or is cited to establish the publication date of another or other special reason (as specified)	cannot be considered involve an inventive s "Y" document of particular	relevance; the claimed invention novel or cannot be considered to tep when the document is taken alone relevance; the claimed invention
"O" docume other r "P" docume	ent referring to an oral disclosure, use, exhibition or	cannot be considered document is combined ments, such combinat in the art.	to involve an inventive step when the d with one or more other such docu-tion being obvious to a person skilled
	actual completion of the international search	"&" document member of the	ne same patent family international search report
	0 May 2000	20/06/200	·
Name and n	nailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer	
	NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Paalman,	R

1

INTERNATIONAL SEARCH REPORT

Intern. ial Application No
PCT/EP 00/01403

C (C	Miss) DOCUMENTS CONGRESS TO THE TOTAL TO THE	PCT/EP 00	7/01403
Category °	Citation of document, with indication where accounts		
Category *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
A	US 4 812 500 A (HAYDEN EARL E) 14 March 1989 (1989-03-14) cited in the application column 5, line 29 - line 31		1
A	EP 0 002 616 A (UNIROYAL INC) 27 June 1979 (1979-06-27) page 12, line 1-4 		1

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern: (al Application No
PCT/EP 00/01403

	ocument arch report		Publication date		Patent family member(s)	Publication date
US 423	3470	Α	11-11-1980	NON		1
GB 143	9009	A	09-06-1976	CA AU BE DE ES FR	988642 A 6313673 A 808125 A 2360114 A 421095 A 2209181 A	04-05-1976 05-06-1975 04-06-1974 06-06-1974 01-04-1976 28-06-1974
**************************************	**************************************	-		IT JP JP JP SE	1006120 B 1072175 C 49087737 A 55032734 B 411809 B	30-09-1976 30-11-1981 22-08-1974 27-08-1980 04-02-1980
WO 932	4935	Α	09-12-1993	MX	9303053 A	01-11-1993
WO 932	4938	Α	09-12-1993	MX	9303054 A	01-11-1993
US 481	2500	А	14-03-1989	AT AU CA DE DK EP FI JP JP KR NZ	117339 T 2298988 A 1334228 A 3852803 D 3852803 T 543588 A 0310393 A 884489 A,B, 1103638 A 2603309 B 9615630 B 226390 A	15-02-1995 06-04-1989 31-01-1995 02-03-1995 24-05-1995 31-03-1989 05-04-1989 20-04-1989 23-04-1997 18-11-1996 28-08-1990
EP 000	2616	A	27-06-1979	US US CA DE JP JP JP	4145556 A 4154723 A 1151204 A 2862220 D 1371403 C 54090143 A 61036746 B	20-03-1979 15-05-1979 02-08-1983 05-05-1983 07-04-1987 17-07-1979 20-08-1986